RZR® 900 vs. ARCTIC CAT® WILDCAT™ TRAIL HEAD-TO-HEAD

POWER

- **19**% More Horsepower† The most powerful in the 50" Class.
- **0 40** in **3.76** Seconds Almost a full second faster.
- **Electronic Throttle Control** Compensates for changes in elevation, maintaining peak power wherever you ride.

SUSPENSION

- **11" of Ground Clearance** An inch more than the competition keeps you riding high above the rough stuff.
- **26" Polaris PXT Tire** The proven Polaris tire is now an inch taller for more comfort and increased ride height.

AGILITY

- **High Performance True On-Demand All-Wheel Drive** Engages all 4 tires faster than the competition and without locking the differential.
- Optimized Track Width Nearly 4" wider for a more planted & confident feel in the corners.
- Narrow Turning Radius Over a foot narrower for easier maneuvering in tight terrain.
- VersaTrac[™] Turf Mode Polaris exclusive feature offered on all Trail models.

CUSTOMIZATION & COMFORT

- **Electronic Power Steering** Available on all Trail models.
- Wider Cockpit More elbow room for you and your passenger.
- Exclusive Lock & Ride® Technology Quickly install accessories in seconds.









	Polaris <i>RZR</i> ® 900 ADVANTAGE	<i>RZR®</i> 900	Arctic Cat® Wildcat™ Trail	
Engine Type	V	4-Stroke DOHC Twin Cylinder	4-Stroke Twin Cylinder	
Displacement		875 cc	700 cc	
Fuel System		Electronic Fuel Injection	Electronic Fuel Injection	
Cooling System		Liquid	Liquid	
Transmission/Final Drive		Automatic PVT P/R/N/L/H	Hi/Lo Range, Reverse & Park	
Drive System	V .	On-Demand True AWD/2WD (High Performance AWD Available on Trail Models)	2/4 WD + Electric Front Differential Lock	
Engine Braking System		Not Equipped (EBS Available on Trail Models)	N/A	
Front Suspension		Dual A-Arm with Anti-Sway Bar 10" (25.4 cm) Travel	Dual A-Arm with Anti-Sway Bar 10" (25.4 cm) Travel	
Rear Suspension		Dual A-Arm with Anti-Sway Bar 10" (25.4 cm) Travel	Dual A-Arm with Anti-Sway Bar 10.5" (25.4 cm) Travel	
Front/Rear Brakes		4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	Hydraulic Disc/Dual Wheel Hydraulic Disc	
Parking Brake		Park in Transmission	Park in Transmission	
Front Tires	✓	26 x 8-12" PXT	25 x 8-12"	
Rear Tires	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	26 x 9-12" PXT	25 x 10-12"	
Wheels		Stamped Steel (Aluminum Available on Trail Models)	Steel	
Wheelbase		79" (200.7 cm)	84.6" (214.9 cm)	
Dry Weight	YEAR TO THE	1,148 lbs (520.7 kg)	990 lbs (449.1 kg)	
Overall Vehicle Size (L x W x H)		105 x 50 x 69.5" (266.7 x 127 x 176.5 cm)	110.5 x 50 x 64.3" (280.7 x 127 x 163.3 cm)	
Ground Clearance	「愛 ノ 袋」	11" (27.9 cm)**	10" (25.4 cm)	
Fuel Capacity	1 3 V Eq.	9.5 gal (36.0 L)	7.4 gal (28.0 L)	
Bed Box Dimensions (L x W x H)	A V Aller	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	N.A.	
Front/Rear Rack or Box Capacity		300 lbs (136.1 kg)	300 lbs (136.1 kg)	
Payload Capacity		740 lbs (335.6 kg)	N.A.	
Hitch Towing Rating		1,500 lbs (680.4 kg)	1,500 lbs (680.4 kg)	
Hitch/Type		Standard/1.25" Receiver	Standard/2" Receiver	
Cargo System	₹ ✓ 50	Lock & Ride®	N.A.	
Lighting		Halogen, 55W Low/ 60W High	N.A.	
Electronic Power Steering	✓	Available on Trail Models	N.A.	
Instrumentation	-	Digital Gauge, Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, DC Outlet	Digital Speedometer/Odometer	
Colors	1	White Lightning*, Polaris Pursuit Camo*, Black Pearl, Sunset Red	Green, Lime, Red	

^{*}Feature may vary on Base / Trail models. **With adjustable suspension. See Owner's Manual for details.